

Appendix F Traffic Data

Appendix F1

Existing 2000

Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 AM Peak

Scenario Report

Existing 2000 AM Peak
 Command: Existing 2000 AM Peak
 Volume: Existing 2000 AM Peak
 Geometry: Existing
 Impact Fee: Default
 Trip Generation: None
 Trip Distribution: Existing
 Paths: Existing
 Routes: Default Routes
 Configuration: Existing 2000 AM Peak

Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 AM Peak

Impact Analysis Report
 Level Of Service

Intersection	Base Del./ LOS Veh C	V/ V/ C	Future Del./ LOS Veh C	Change in
# 17 Figueroa St / Harry Bridges Bl	A xxxxxx 0.362	A xxxxxx 0.362	A xxxxxx 0.362	+ 0.000 V/C
# 21 Avalon Ave / Harry Bridges Blv	A xxxxxx 0.294	A xxxxxx 0.294	A xxxxxx 0.294	+ 0.000 V/C
# 23 Alameda St / Anaheim St	A xxxxxx 0.513	A xxxxxx 0.513	A xxxxxx 0.513	+ 0.000 V/C
# 26 Henry Ford Ave / Anaheim St	A xxxxxx 0.409	A xxxxxx 0.409	A xxxxxx 0.409	+ 0.000 V/C
# 31 Harbor Blvd / SR-47 WB On-Ramp	A 8.9 0.000	A 8.9 0.000	A 8.9 0.000	+ 0.000 D/V
# 32 Harbor Blvd / SR 47 EB Off-Ram	C xxxxxx 0.703	C xxxxxx 0.703	C xxxxxx 0.703	+ 0.000 V/C
# 34 John S. Gibson / I-110 NB Ram	A xxxxxx 0.503	A xxxxxx 0.503	A xxxxxx 0.503	+ 0.000 V/C
# 37 Figueroa St / C-St / I-110 Ram	C 17.4 0.678	C 17.4 0.678	C 17.4 0.678	+ 0.000 V/C
# 53 Pacific Ave / Front St	A xxxxxx 0.463	A xxxxxx 0.463	A xxxxxx 0.463	+ 0.000 V/C
# 72 Fries Ave / Harry Bridges Blvd	A xxxxxx 0.259	A xxxxxx 0.259	A xxxxxx 0.259	+ 0.000 V/C
# 73 Neptune Ave / Harry Bridges Bl	A xxxxxx 0.186	A xxxxxx 0.186	A xxxxxx 0.186	+ 0.000 V/C
# 92 ICTF Driveway # 1 / Sepulveda	A xxxxxx 0.312	A xxxxxx 0.312	A xxxxxx 0.312	+ 0.000 V/C
# 93 ICTF Driveway # 2 / Sepulveda	A xxxxxx 0.354	A xxxxxx 0.354	A xxxxxx 0.354	+ 0.000 V/C
# 94 Santa Fe Ave / Anaheim St	A xxxxxx 0.336	A xxxxxx 0.336	A xxxxxx 0.336	+ 0.000 V/C
#110 John S. Gibson / Channel Stree	A xxxxxx 0.514	A xxxxxx 0.514	A xxxxxx 0.514	+ 0.000 V/C
#128 Broad Ave / Harry Bridges Blvd	A xxxxxx 0.212	A xxxxxx 0.212	A xxxxxx 0.212	+ 0.000 V/C
#212 Navy Way / Seaside Ave	A xxxxxx 0.504	A xxxxxx 0.504	A xxxxxx 0.504	+ 0.000 V/C

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #17 Figueroa St / Harry Bridges Blvd
Cycle (sec): 100 Critical Vol./Cap.(X): 0.362
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 23 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control:		Permitted		Permitted		Permitted	
Rights:		Ignore		Include		Ignore	
Min. Green:		0		0		0	
Lanes:		0 1 0 1 0 1 0 2 0 1		1 0 1 1 0 1 0 1 0 2 0 1		1 0 2 0 1	

Volume Module:

Base Vol:	32	92	31	201	233	112	53	354	17	131	369	202
Growth Adj:	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91
Initial Bse:	29	84	28	184	213	102	48	323	16	120	337	184
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	29	84	28	184	213	0	48	323	16	120	337	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	29	84	28	184	213	0	48	323	16	120	337	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	29	84	28	184	213	0	48	323	16	120	337	0

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.41	1.19	0.40	1.00	2.00	1.00	1.00	1.91	0.09	1.00	2.00	1.00
Final Sat.:	619	1781	600	1500	3000	1500	1500	2863	137	1500	3000	1500

Capacity Analysis Module:

Vol/Sat:	0.05	0.05	0.05	0.12	0.07	0.00	0.03	0.11	0.11	0.08	0.11	0.00
Crit Vol:	71	184	184	169	169	120	120	120	120	120	120	120
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #21 Avalon Ave / Harry Bridges Blvd
Cycle (sec): 100 Critical Vol./Cap.(X): 0.294
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 20 Level Of Service: A
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control:		Permitted		Permitted		Permitted	
Rights:		Include		Include		Include	
Min. Green:		0		0		0	
Lanes:		0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0		0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0		0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0	

Volume Module:

Base Vol:	38	37	8	10	29	44	87	305	30	11	428	47
Growth Adj:	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06
Initial Bse:	40	39	8	11	31	47	92	323	32	12	453	50
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	40	39	8	11	31	47	92	323	32	12	453	50
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	40	39	8	11	31	47	92	323	32	12	453	50
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	40	39	8	11	31	47	184	323	32	23	453	50

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.92	0.89	0.19	0.24	0.76	1.00	0.52	1.36	0.12	0.05	1.76	0.19
Final Sat.:	1373	1337	289	361	1139	1500	779	2044	177	69	2647	284

Capacity Analysis Module:

Vol/Sat:	0.03	0.03	0.03	0.03	0.03	0.03	0.12	0.16	0.18	0.17	0.17	0.18
Crit Vol:	40	47	92	92	92	92	92	92	92	92	92	92
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #23 Alameda St. / Anaheim St.
Cycle (sec): 100 Critical Vol./Cap.(X): 0.513
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 38 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Permitted Permitted
Rights: Owl Include Include Include
Min. Green: 0 0 0 0 0 0 0 0
Lanes: 1 0 1 1 1 0 2 0 1 1 0 2 0 1 2 0 1 1 0

Volume Module:
Base Vol: 11 124 268 4 198 79 84 783 12 324 591 20
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 12 131 284 4 209 84 89 828 13 343 625 21
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 12 131 284 4 209 84 89 828 13 343 625 21
Reduc Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 12 131 284 4 209 84 89 828 13 343 625 21
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol.: 12 131 284 4 209 84 89 828 13 343 625 21

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.00 2.00 1.00 2.00 1.00 2.00 1.00 2.00 1.93 0.07
Final Sat.: 1425 1425 2850 1425 2850 1425 2850 1425 2850 2757 93

Capacity Analysis Module:
Vol/Sat: 0.01 0.09 0.10 0.00 0.07 0.06 0.06 0.29 0.01 0.12 0.23 0.23
Crit Vol: 142 4
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #26 Henry Ford Ave / Anaheim St.
Cycle (sec): 100 Critical Vol./Cap.(X): 0.409
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 31 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Permitted Permitted
Rights: Include Include Ignore Include
Min. Green: 0 0 0 0 0 0 0 0
Lanes: 1 1 1 0 1 1 0 2 1 0 1 0 2 0 1 1 0 2 0 1

Volume Module:
Base Vol: 138 60 82 36 94 12 9 767 238 50 606 66
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 146 63 87 38 99 13 10 811 252 53 641 70
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 146 63 87 38 99 13 10 811 252 53 641 70
Reduc Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 146 63 87 38 99 13 10 811 252 53 641 70
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol.: 146 63 87 38 99 13 10 811 252 53 641 70

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 2.00 1.00 1.00 1.00 2.66 0.34 1.00 2.00 1.00 1.00 2.00 1.00
Final Sat.: 2850 1425 1425 1425 3791 484 1425 2850 1425 1425 2850 1425

Capacity Analysis Module:
Vol/Sat: 0.05 0.04 0.06 0.03 0.03 0.03 0.01 0.28 0.00 0.04 0.22 0.05
Crit Vol: 87 38
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
 2000 HCM Unsignalized Method (Base Volume Alternative)

 Intersection #31 Harbor Blvd / SR-47 WB On-Ramp

 Average Delay (sec/veh): 5.0 Worst Case Level of Service: A[8.9]

 Approach: North Bound East Bound West Bound
 Movement: L - T - R L - T - R L - T - R L - T - R
 Control: Uncontrolled Uncontrolled Stop Sign Stop Sign
 Rights: Include Include Include Include
 Lanes: 1 0 2 0 0 0 1 1 0 0 0 0 0 0 0 0 0 0 0 0
 Volume Module:
 Base Vol: 475 218 0 0 156 5 0 0 0 0 0 0 0 0 0
 Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
 Initial Bse: 503 231 0 0 165 5 0 0 0 0 0 0 0 0 0
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Volume: 503 231 0 0 165 5 0 0 0 0 0 0 0 0 0
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0
 Final Vol.: 503 231 0 0 165 5 0 0 0 0 0 0 0 0 0
 Critical Gap Module:
 Critical Gap: 4.1 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 FollowUpTin: 2.2 xxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Capacity Module:
 Chflct Vol: 170 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Potent Cap.: 1419 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Move Cap.: 1419 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Volume/Cap: 0.35 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Level of Service Module:
 2Way95thQ: 1.6 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Control Del: 8.9 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 LOS By Move: A * * * * *
 Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT
 Shared Cap.: xxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 SharedQueue: xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Shrd ConDel: xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx
 Shared LOS: * * * * *
 ApproachDel: xxxxxx * xxxxxx *
 ApproachLOS: * * * * *
 Note: Queue reported is the number of cars per lane.

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
 Circular 212 Planning Method (Base Volume Alternative)

 Intersection #32 Harbor Blvd / SR 47 EB Off-Ramp / Swinford St

 Cycle (sec): 100 Critical Vol./Cap.(X): 0.703
 Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
 Optimal Cycle: 77 Level Of Service: C

 Approach: North Bound South Bound East Bound West Bound
 Movement: L - T - R L - T - R L - T - R L - T - R
 Control: Protected Protected Split Phase Split Phase
 Rights: Include Ovl Include Ovl
 Lanes: 1 0 2 1 0 1 0 1 0 1 0 0 0 0 0 0 0 0 0 0
 Volume Module:
 Base Vol: 289 603 25 26 112 45 79 54 813 19 12 12
 Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
 Initial Bse: 306 638 26 28 118 48 84 57 860 20 13 13
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Volume: 306 638 26 28 118 48 84 57 860 20 13 13
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0
 Reduced Vol: 306 638 26 28 118 48 84 57 860 20 13 13
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Final Vol.: 306 638 26 28 118 48 84 57 860 20 13 13
 Saturation Flow Module:
 Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Lanes: 1.00 2.88 0.12 1.00 1.43 0.57 1.19 0.81 1.00 0.88 0.56 0.56
 Final Sat.: 1375 3961 164 1375 1962 788 1633 1117 1375 1215 767 767
 Capacity Analysis Module:
 Vol/Sat: 0.22 0.16 0.16 0.02 0.06 0.06 0.05 0.05 0.63 0.02 0.02 0.02
 Crit Moves: * * * * *

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

 Intersection #34 John S. Gibson / I-110 NB Ramps
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.503
 Loss Time (sec): 37 Average Delay (sec/veh): xxxxxx
 Optimal Cycle: 37 Level Of Service: A
 Approach: North Bound East Bound West Bound
 Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R
 Control: Protected Protected Permitted Permitted
 Rights: Include Include Include Include
 Min. Green: 0 0 0 0
 Lanes: 2 0 1 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0
 Volume Module:
 Base Vol: 753 352 12 58 404 7 15 9 8 20 98 42
 Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
 Initial Bse: 797 372 13 61 427 7 16 10 8 21 104 44
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Volume: 797 372 13 61 427 7 16 10 8 21 104 44
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
 Reduced Vol: 797 372 13 61 427 7 16 10 8 21 104 44
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Final Vol: 797 372 13 61 427 7 16 10 8 21 104 44
 Saturation Flow Module:
 Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Lanes: 2.00 1.93 0.07 1.00 1.97 0.03 1.00 0.53 0.47 0.25 1.23 0.52
 Final Sat.: 2850 2756 94 1425 2801 49 1425 754 671 356 1746 748
 Capacity Analysis Module:
 Vol/Sat: 0.28 0.14 0.14 0.04 0.15 0.15 0.01 0.01 0.01 0.06 0.06 0.06
 Crit Moves: 398 217 16 *****
 Delay/Veh: 23.2 9.9 0.0 0.0 10.6 10.2 16.9 16.3 16.3 0.0 0.0 9.7
 AdjDel/Veh: 23.2 9.9 0.0 0.0 10.6 10.2 16.9 16.3 16.3 0.0 0.0 9.7
 LOS by Move: C A * * B B C C C * * A
 ApproachDel: 21.1 10.5 17.0 17.0 9.7
 Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 ApprAdjDel: 21.1 10.5 17.0 17.0 9.7
 LOS by Appr: C C B B C C A A
 AllWayAvgG: 1.8 0.1 0.0 0.0 0.2 0.1 1.1 1.1 1.1 0.0 0.0 0.0
 Note: Queue reported is the number of cars per lane.

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
2000 HCM 4-Way Stop Method (Base Volume Alternative)

 Intersection #37 Figueroa St / C-St / I-110 Ramps
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.678
 Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): 17.4
 Optimal Cycle: 0 Level Of Service: C
 Approach: North Bound South Bound East Bound West Bound
 Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R
 Control: Stop Sign Stop Sign Stop Sign Stop Sign
 Rights: Include Include Include Include
 Min. Green: 0 0 0 0
 Lanes: 1 0 2 0 0 0 1 0 1 0 1 0 0 0 0 0 0 0 0 0 1
 Volume Module:
 Base Vol: 312 60 0 106 37 378 0 192 0 192 0 0 13
 Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
 Initial Bse: 330 63 0 112 39 400 0 203 0 203 0 0 14
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Volume: 330 63 0 112 39 400 0 203 0 203 0 0 14
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0
 Reduced Vol: 330 63 0 112 39 400 0 203 0 203 0 0 14
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Final Vol: 330 63 0 112 39 400 0 203 0 203 0 0 14
 Saturation Flow Module:
 Sat/Lane: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Adjustment: 1.00 2.00 0.00 0.00 1.48 0.52 1.33 xxxxx 0.67 0.00 0.00 1.00
 Lanes: 487 1029 0 0 754 272 1256 550 371 0 0 503
 Final Sat.: 487 1029 0 0 754 272 1256 550 371 0 0 503
 Capacity Analysis Module:
 Vol/Sat: 0.68 0.06 xxxxx 0.15 0.14 0.32 0.00 0.55 xxxxx xxxxx 0.03
 Crit Moves: *****
 Delay/Veh: 23.2 9.9 0.0 0.0 10.6 10.2 16.9 16.3 16.3 0.0 0.0 9.7
 AdjDel/Veh: 23.2 9.9 0.0 0.0 10.6 10.2 16.9 16.3 16.3 0.0 0.0 9.7
 LOS by Move: C A * * B B C C C * * A
 ApproachDel: 21.1 10.5 17.0 17.0 9.7
 Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 ApprAdjDel: 21.1 10.5 17.0 17.0 9.7
 LOS by Appr: C C B B C C A A
 AllWayAvgG: 1.8 0.1 0.0 0.0 0.2 0.1 1.1 1.1 1.1 0.0 0.0 0.0
 Note: Queue reported is the number of cars per lane.

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #53 Pacific Ave / Front St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.463
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 40 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Protected Protected Permitted
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 1 0 0 1 0 0 0 0 0 2 0 1 1 0 2 0 0

Volume Module:
Base Vol: 533 0 26 0 0 0 380 437 23 236 0
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 487 0 24 0 0 0 347 399 21 215 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 487 0 24 0 0 0 347 399 21 215 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 487 0 24 0 0 0 347 399 21 215 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 487 0 24 0 0 0 347 399 21 215 0

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 0.00 1.00 0.00 0.00 2.00 1.00 1.00 2.00 0.00
Final Sat.: 1425 0 1425 0 0 0 0 2850 1425 2850 0

Capacity Analysis Module:
Vol/Sat: 0.34 0.00 0.02 0.00 0.00 0.00 0.00 0.12 0.28 0.01 0.08 0.00
Crit Vol: 487 0 173 108
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #72 Fries Ave / Harry Bridges Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.259
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 19 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Permitted Permitted
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 0 1 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0

Volume Module:
Base Vol: 102 22 48 7 15 11 19 351 66 57 460 1
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 93 20 44 6 14 10 17 320 60 52 420 1
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 93 20 44 6 14 10 17 320 60 52 420 1
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 93 20 44 6 14 10 17 320 60 52 420 1
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol.: 93 20 44 6 14 10 17 320 60 104 420 1

Saturation Flow Module:
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 0.44 0.56 0.42 0.91 0.67 0.09 1.62 0.29 0.24 1.75 0.01
Final Sat.: 1500 663 837 636 1364 1000 137 2428 435 371 2624 5

Capacity Analysis Module:
Vol/Sat: 0.06 0.03 0.05 0.01 0.01 0.01 0.13 0.13 0.14 0.14 0.16 0.17
Crit Vol: 93 15 17 17
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #73 Neptune Ave / Harry Bridges Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.186
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 18 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted	Permitted	Permitted	Permitted	Protected	Protected
Rights:	Include	Include	Include	Include	Include	Include
Min. Green:	0	0	0	0	0	0
Lanes:	0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0	0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0	0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0	0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0	0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0	0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0

Volume Module:

Base Vol:	0	0	2	0	29	20	440	0	0	513	1
Growth Adj:	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91
Initial Bse:	0	0	2	0	26	18	402	0	0	468	1
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	0	0	2	0	26	18	402	0	0	468	1
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	0	2	0	26	18	402	0	0	468	1
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	0	0	2	0	26	37	402	0	0	468	1

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.00	2.00	0.00	0.13	0.87	1.00	0.18	1.82	0.00	0.00	1.99
Final Sat.:	0	3000	0	194	1306	1500	273	2727	0	0	2994

Capacity Analysis Module:

Vol/Sat:	0.00	0.00	0.00	0.01	0.00	0.02	0.07	0.15	0.00	0.00	0.16
Crit Vol:	0	26	18	402	0	468	0	0	0	0	468
Crit Moves:	0	0	0	0	0	0	0	0	0	0	0

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #92 ICTF Driveaway # 1 / Sepulveda Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.312
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 27 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted	Permitted	Permitted	Permitted	Protected	Protected
Rights:	Include	Include	Include	Include	Include	Include
Min. Green:	0	0	0	0	0	0
Lanes:	0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0	0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0	0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0	0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0	0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0	0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0

Volume Module:

Base Vol:	21	0	25	199	0	64	74	523	23	37	454
Growth Adj:	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91
Initial Bse:	19	0	23	182	0	58	68	477	21	34	415
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	19	0	23	182	0	58	68	477	21	34	415
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	19	0	23	182	0	58	68	477	21	34	415
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	19	0	23	182	0	58	68	477	21	34	415

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.46	0.00	0.54	1.51	0.01	0.48	1.00	1.92	0.08	1.00	2.99
Final Sat.:	651	0	774	2156	0	694	1425	2730	120	1425	4256

Capacity Analysis Module:

Vol/Sat:	0.03	0.00	0.03	0.08	0.00	0.08	0.05	0.17	0.17	0.02	0.10
Crit Vol:	42	120	42	120	42	120	249	34	34	34	34
Crit Moves:	0	0	0	0	0	0	0	0	0	0	0

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #93 ICTF Driveway # 2 / Sepulveda Blvd
Cycle (sec): 100 Critical Vol./Cap.(X): 0.354
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 29 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Include Protected Include Protected Include
Rights: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Min. Green: 1 0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0 2 1 0
Lanes: 1 0 0 1 0 1 0 0 1 0 1 0 1 0 1 0 1 0 2 1 0

Volume Module:
Base Vol: 51 2 89 9 0 1 2 661 65 90 450 6
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 47 2 81 8 0 1 2 603 59 82 411 5
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 47 2 81 8 0 1 2 603 59 82 411 5
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 47 2 81 8 0 1 2 603 59 82 411 5
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 47 2 81 8 0 1 2 603 59 82 411 5

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 0.02 0.98 1.00 0.00 1.00 1.00 1.82 0.18 1.00 2.96 0.04
Final Sat: 1425 31 1394 1425 0 1425 1425 2595 255 1425 4219 56

Capacity Analysis Module:
Vol/Sat: 0.03 0.06 0.06 0.01 0.00 0.00 0.00 0.23 0.23 0.06 0.10 0.10
Crit Vol: 83 8 331 82
Crit Moves: *****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #94 Santa Fe Ave / Anaheim St
Cycle (sec): 100 Critical Vol./Cap.(X): 0.336
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 34 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Include Protected Include Protected Include
Rights: 0 0 0 0 0 0 0 0 0 0 0 0
Min. Green: 1 0 1 1 0 1 0 1 0 1 0 2 1 0 1 0 3 0 1
Lanes: 1 0 1 1 0 1 0 1 0 1 0 2 1 0 1 0 3 0 1

Volume Module:
Base Vol: 40 102 38 75 102 65 42 723 23 43 705 165
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 42 108 40 79 108 69 44 765 24 45 746 175
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 42 108 40 79 108 69 44 765 24 45 746 175
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 42 108 40 79 108 69 44 765 24 45 746 175
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 42 108 40 79 108 69 44 765 24 45 746 175

Saturation Flow Module:
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.46 0.54 1.00 1.22 0.78 1.00 2.91 0.09 1.00 3.00 1.00
Final Sat: 1375 2004 746 1375 1680 1070 1375 3998 127 1375 4125 1375

Capacity Analysis Module:
Vol/Sat: 0.03 0.05 0.05 0.06 0.06 0.06 0.03 0.19 0.19 0.03 0.18 0.13
Crit Vol: 74 79 263 45
Crit Moves: *****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #110 John S. Gibson / Channel Street

Cycle (sec): 100 Critical Vol./Cap.(X): 0.514
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 38 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted		Protected		Permitted		Permitted	
	Include	Exclude	Include	Exclude	Include	Exclude	Include	Exclude
Rights:	0	0	0	0	0	0	0	0
Min. Green:	1	0	2	0	1	0	1	0
Lanes:	1	0	2	0	1	0	1	0

Volume Module:

Base Vol:	290	454	0	0	289	187	651	0	282	0	0	0
Growth Adj:	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91
Initial Bse:	265	415	0	0	264	171	594	0	257	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	265	415	0	0	264	171	594	0	257	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	265	415	0	0	264	171	594	0	257	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	265	415	0	0	264	171	594	0	257	0	0	0

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.00	0.00	2.00	1.00	2.00	0.00	1.00	0.00	0.00	0.00	0.00
Final Sat.:	1425	2850	0	2850	1425	2850	0	1425	0	0	0	0

Capacity Analysis Module:

Vol/Sat:	0.19	0.15	0.00	0.00	0.09	0.12	0.21	0.00	0.18	0.00	0.00	0.00
Crit Vol:	265	415	0	415	297	171	594	0	257	0	0	0
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 AM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #128 Broad Ave / Harry Bridges Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.212
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 18 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted		Protected		Permitted		Permitted	
	Include	Exclude	Include	Exclude	Include	Exclude	Include	Exclude
Rights:	0	0	0	0	0	0	0	0
Min. Green:	0	1	0	0	0	0	0	0
Lanes:	0	1	0	0	0	0	0	0

Volume Module:

Base Vol:	1	8	20	18	5	81	47	248	3	51	377	11
Growth Adj:	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91
Initial Bse:	1	7	18	16	5	74	43	226	3	47	344	10
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	1	7	18	16	5	74	43	226	3	47	344	10
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	1	7	18	16	5	74	43	226	3	47	344	10
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	1	7	18	16	5	74	86	226	3	47	344	10

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.07	0.93	1.00	0.35	0.65	1.00	0.37	1.61	0.02	0.23	1.72	0.05
Final Sat.:	103	1397	1500	519	981	1500	562	2412	26	349	2576	75

Capacity Analysis Module:

Vol/Sat:	0.01	0.01	0.01	0.03	0.00	0.05	0.08	0.09	0.10	0.13	0.13	0.13
Crit Vol:	1	7	18	74	43	74	43	43	43	43	43	200
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 AM Peak

Level of Service Computation Report
 Circular 212 Planning Method (Base Volume Alternative)

 Intersection #212 Navy Way / Seaside Ave
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.504
 Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
 Optimal Cycle: 38 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound

Movement	L	T	R	L	T	R	L	T	R	L	T	R					
Control:	Permitted			Permitted			Protected			Protected							
Rights:	Ignore			Include			Include			Include							
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0					
Lanes:	2	0	0	1	0	0	0	0	0	3	0	1	2	0	3	0	0

Volume Module:

Base Vol:	46	0	501	0	0	0	0	1387	67	387	1191	0
Growth Adj:	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06
Initial Bse:	49	0	530	0	0	0	1467	71	409	1260	0	0
User Adj:	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	49	0	0	0	0	0	1467	71	409	1260	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	49	0	0	0	0	0	1467	71	409	1260	0	0
PCE Adj:	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	49	0	0	0	0	0	1467	71	409	1260	0	0

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	2	0	0	0	0	0	3	0	1	2	0	3
Final Sat.:	2850	0	1425	0	0	0	4275	1425	2850	4275	0	0

Capacity Analysis Module:

Vol/Sat:	0.02	0.00	0.00	0.00	0.00	0.00	0.34	0.05	0.14	0.29	0.00	0.00
Crit Vol:	24	0	0	0	0	0	489	205	489	205	0	0
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 PM Peak

Scenario Report

Existing 2000 PM Peak
 Command: Existing 2000 PM Peak
 Volume: Existing 2000 PM Peak
 Geometry: Existing
 Impact Fee: Default
 Trip Generation: None
 Trip Distribution: Existing
 Paths: Existing
 Routes: Default Routes
 Configuration: Existing 2000 PM Peak

Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 PM Peak

Impact Analysis Report
 Level Of Service

Intersection	Base Del./ LOS Veh C	V/ V/ C	Future Del./ LOS Veh C	Change in
# 17 Figueroa St / Harry Bridges Bl	A xxxxx 0.398	A xxxxx 0.398	A xxxxx 0.398	+ 0.000 V/C
# 21 Avalon Ave / Harry Bridges Blv	A xxxxx 0.310	A xxxxx 0.310	A xxxxx 0.310	+ 0.000 V/C
# 23 Alameda St / Anaheim St	A xxxxx 0.484	A xxxxx 0.484	A xxxxx 0.484	+ 0.000 V/C
# 26 Henry Ford Ave / Anaheim St	A xxxxx 0.574	A xxxxx 0.574	A xxxxx 0.574	+ 0.000 V/C
# 31 Harbor Blvd / SR-47 WB On-Ramp	A 9.2 0.000	A 9.2 0.000	A 9.2 0.000	+ 0.000 D/V
# 32 Harbor Blvd / SR 47 EB Off-Ram	C xxxxx 0.722	C xxxxx 0.722	C xxxxx 0.722	+ 0.000 V/C
# 34 John S. Gibson / I-110 NB Ram	A xxxxx 0.468	A xxxxx 0.468	A xxxxx 0.468	+ 0.000 V/C
# 37 Figueroa St / C-St / I-110 Ram	C 21.3 0.673	C 21.3 0.673	C 21.3 0.673	+ 0.000 V/C
# 53 Pacific Ave / Front St	A xxxxx 0.403	A xxxxx 0.403	A xxxxx 0.403	+ 0.000 V/C
# 72 Fries Ave / Harry Bridges Blvd	A xxxxx 0.338	A xxxxx 0.338	A xxxxx 0.338	+ 0.000 V/C
# 73 Neptune Ave / Harry Bridges Bl	A xxxxx 0.284	A xxxxx 0.284	A xxxxx 0.284	+ 0.000 V/C
# 92 ICTF Driveway # 1 / Sepulveda	A xxxxx 0.516	A xxxxx 0.516	A xxxxx 0.516	+ 0.000 V/C
# 93 ICTF Driveway # 2 / Sepulveda	A xxxxx 0.398	A xxxxx 0.398	A xxxxx 0.398	+ 0.000 V/C
# 94 Santa Fe Ave / Anaheim St	A xxxxx 0.470	A xxxxx 0.470	A xxxxx 0.470	+ 0.000 V/C
#110 John S. Gibson / Channel Stree	B xxxxx 0.600	B xxxxx 0.600	B xxxxx 0.600	+ 0.000 V/C
#128 Broad Ave / Harry Bridges Blvd	A xxxxx 0.285	A xxxxx 0.285	A xxxxx 0.285	+ 0.000 V/C
#212 Navy Way / Seaside Ave	A xxxxx 0.472	A xxxxx 0.472	A xxxxx 0.472	+ 0.000 V/C

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #17 Figueroa St / Harry Bridges Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.398
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 24 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted	Permitted	Permitted		Permitted	Permitted
			Include	Ignore		
Rights:	0	0	0	0	0	0
Min. Green:	0	0	0	0	0	0
Lanes:	0	1	0	1	0	1

Volume Module:

Base Vol:	39	142	88	84	81	500	13	45	415	274
Growth Adj:	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91	0.91
Initial Bse:	36	130	80	199	80	77	74	457	12	41
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	36	130	80	199	80	74	457	12	41	379
Reduct Vol:	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	36	130	80	199	80	74	457	12	41	379
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MUF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	36	130	80	199	80	74	457	12	41	379

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.29	1.06	0.65	1.00	2.00	1.00	1.00	1.95	0.05	1.00
Final Sat.:	435	1584	981	1500	3000	1500	1500	2924	76	1500

Capacity Analysis Module:

Vol/Sat:	0.08	0.08	0.08	0.13	0.03	0.00	0.05	0.16	0.16	0.03
Crit Vol:	123	199	199	234	41	234	41	234	41	234
Crit Moves:	****	****	****	****	****	****	****	****	****	****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #21 Avalon Ave / Harry Bridges Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.310
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 21 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted	Permitted	Permitted		Permitted	Permitted
			Include	Include		
Rights:	0	0	0	0	0	0
Min. Green:	0	1	0	1	0	1
Lanes:	0	1	0	1	0	1

Volume Module:

Base Vol:	40	49	9	13	36	97	89	360	46	10
Growth Adj:	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06
Initial Bse:	42	52	10	14	38	103	94	381	49	11
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	42	52	10	14	38	103	94	381	49	11
Reduct Vol:	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	42	52	10	14	38	103	94	381	49	11
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MUF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol:	42	52	10	14	38	103	188	381	49	21

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.82	1.00	0.18	0.18	0.82	1.00	0.44	1.40	0.16	0.06
Final Sat.:	1224	1500	276	267	1233	1500	658	2106	236	87

Capacity Analysis Module:

Vol/Sat:	0.03	0.03	0.03	0.05	0.03	0.07	0.14	0.18	0.21	0.12
Crit Vol:	42	103	103	309	11	309	11	309	11	309
Crit Moves:	****	****	****	****	****	****	****	****	****	****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #23 Alameda St / Anaheim St
Cycle (sec): 100 Critical Vol./Cap.(X): 0.484
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 36 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Permitted Permitted
Rights: Owl Include Include Include
Min. Green: 0 0 0 0 0 0 0 0
Lanes: 1 0 1 1 1 0 2 0 1 1 0 2 0 1 2 0 1 1 0

Volume Module:
Base Vol: 7 241 386 10 181 116 74 596 13 270 719 29
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 7 255 408 11 191 123 78 631 14 286 761 31
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 7 255 408 11 191 123 78 631 14 286 761 31
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 7 255 408 11 191 123 78 631 14 286 761 31
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 7 255 408 11 191 123 78 631 14 286 761 31

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.15 1.85 1.00 2.00 1.00 1.00 2.00 1.00 2.00 1.92 0.08
Final Sat: 1425 1643 2632 1425 2850 1425 1425 2850 1425 2850 2740 110

Capacity Analysis Module:
Vol/Sat: 0.01 0.16 0.16 0.01 0.07 0.09 0.05 0.22 0.01 0.10 0.28 0.28
Crit Vol: 221 11 315 143
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #26 Henry Ford Ave / Anaheim St
Cycle (sec): 100 Critical Vol./Cap.(X): 0.574
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 44 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Permitted Permitted
Rights: Include Include Ignore Include
Min. Green: 0 0 0 0 0 0 0 0
Lanes: 1 1 1 0 1 1 0 2 1 0 1 0 2 0 1 1 0 2 0 1

Volume Module:
Base Vol: 326 235 34 82 76 25 14 939 151 34 767 79
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 345 249 36 87 80 26 15 993 160 36 811 84
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 345 249 36 87 80 26 15 993 0 36 811 84
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 345 249 36 87 80 26 15 993 0 36 811 84
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 345 249 36 87 80 26 15 993 0 36 811 84

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.74 1.26 1.00 1.00 2.26 0.74 1.00 2.00 1.00 1.00 2.00 1.00
Final Sat: 2484 1791 1425 1425 3217 1058 1425 2850 1425 1425 2850 1425

Capacity Analysis Module:
Vol/Sat: 0.14 0.14 0.03 0.06 0.02 0.02 0.01 0.35 0.00 0.03 0.28 0.06
Crit Vol: 198 87 497 36
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #34 John S. Gibson / I-110 NB Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.468
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 35 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Permitted Permitted Permitted
Rights: Include Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 2 0 1 1 0 1 0 1 0 1 0 0 1 0 0 1 0 1 0 0

Volume Module:
Base Vol: 342 353 10 65 543 15 10 5 10 15 180 146
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 362 373 11 69 574 16 11 5 11 16 190 154
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 362 373 11 69 574 16 11 5 11 16 190 154
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 362 373 11 69 574 16 11 5 11 16 190 154
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 362 373 11 69 574 16 11 5 11 16 190 154

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 2.00 1.94 0.06 1.00 1.95 0.05 1.00 0.33 0.67 0.09 1.05 0.86
Final Sat.: 2850 2771 79 1425 2773 77 1425 475 950 125 1504 1220

Capacity Analysis Module:
Vol/Sat: 0.13 0.13 0.13 0.05 0.21 0.21 0.01 0.01 0.01 0.13 0.13 0.13
Crit Moves: 181 295 11 *****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
2000 HCM 4-Way Stop Method (Base Volume Alternative)

Intersection #37 Figueroa St / C-St / I-110 Ramps

Cycle (sec): 100 Critical Vol./Cap.(X): 0.673
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): 21.3
Optimal Cycle: 0 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Stop Sign Stop Sign Stop Sign Stop Sign
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 1 0 2 0 0 0 0 1 0 1 0 1 0 0 0 0 0 0 0 0

Volume Module:
Base Vol: 295 38 0 0 64 36 382 0 382 0 382 0 0 36
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 312 40 0 0 68 38 404 0 404 0 404 0 0 38
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 312 40 0 0 68 38 404 0 404 0 404 0 0 38
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 312 40 0 0 68 38 404 0 404 0 404 0 0 38
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 312 40 0 0 68 38 404 0 404 0 404 0 0 38

Saturation Flow Module:
Sat/Lane: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Adjustment: 1.00 2.00 0.00 0.00 1.28 0.72 1.00 0.00 1.00 0.00 0.00 1.00
Lanes: 464 978 0 0 615 365 1140 601 601 0 0 515
Final Sat.: 464 978 0 0 615 365 1140 601 601 0 0 515

Capacity Analysis Module:
Vol/Sat: 0.67 0.04 xxxxx 0.11 0.10 0.35 0.00 0.67 xxxxx xxxxx 0.07
Crit Moves: *****
Delay/Veh: 23.7 10.1 0.0 0.0 10.7 10.2 22.8 19.6 19.6 0.0 0.0 10.0
AdjDel/Veh: 23.7 10.1 0.0 0.0 10.7 10.2 22.8 19.6 19.6 0.0 0.0 10.0
LOS by Move: C B * * B B C C C * * A
ApproachDel: 22.1 10.5 22.8 10.0
Delay Adj: 1.00 1.00 1.00 1.00
ApprAdjDel: 22.1 10.5 22.8 10.0
LOS by Appr: C B B C
AllWayAvg: 1.7 0.0 0.0 0.0 0.1 0.1 1.8 1.8 1.8 0.1 0.1 0.1
Note: Queue reported is the number of cars per lane.

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #53 Pacific Ave / Front St
Cycle (sec): 100 Critical Vol./Cap.(X): 0.403
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 31 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Protected Protected Permitted Permitted
Rights: Include Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 2 0 1 1 0 2 0 0
Lanes: 1 0 0 0 1 0 0 0 0 0 0 2 0 1 1 0 2 0 0

Volume Module:
Base Vol: 446 0 17 0 0 0 205 634 9 366 0
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 407 0 16 0 0 0 187 579 8 334 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 407 0 16 0 0 0 187 579 8 334 0
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 407 0 16 0 0 0 187 579 8 334 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 407 0 16 0 0 0 187 579 8 334 0

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00
Final Sat: 1425 0 1425 0 0 0 0 2850 1425 1425 2850 0

Capacity Analysis Module:
Vol/Sat: 0.29 0.00 0.01 0.00 0.00 0.00 0.00 0.07 0.41 0.01 0.12 0.00
Crit Vol: 407 0
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #72 Fries Ave / Harry Bridges Blvd
Cycle (sec): 100 Critical Vol./Cap.(X): 0.338
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 22 Level Of Service: A
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Permitted Permitted
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 0 1 0 1 0 0 1 0 1 0 0 1 0 1 0 0 1 0 1 0

Volume Module:
Base Vol: 156 28 156 9 12 34 44 570 33 20 454 7
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 142 26 142 8 11 31 40 520 30 18 415 6
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 142 26 142 8 11 31 40 520 30 18 415 6
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 142 26 142 8 11 31 40 520 30 18 415 6
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 142 26 142 8 11 31 80 520 30 73 415 6

Saturation Flow Module:
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 0.92 0.16 0.92 0.33 0.67 1.00 0.15 1.76 0.09 0.09 1.88 0.03
Final Sat: 1376 247 1376 491 1009 1500 219 2638 143 143 2819 39

Capacity Analysis Module:
Vol/Sat: 0.10 0.10 0.10 0.02 0.01 0.02 0.18 0.20 0.21 0.13 0.15 0.16
Crit Vol: 142 31
Crit Moves: ****

Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 PM Peak

Level of Service Computation Report
 Circular #73 Neptune Ave / Harry Bridges Blvd
 Intersection #73 Neptune Ave / Harry Bridges Blvd
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.284
 Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
 Optimal Cycle: 20 Level Of Service: A
 Approach: North Bound East Bound West Bound
 Movement: L - T - R L - T - R L - T - R L - T - R L - T - R
 Control: Permitted Permitted Permitted Permitted Permitted
 Rights: Include Include Include Include Include
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
 Lanes: 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0
 Volume Module:
 Base Vol: 0 0 0 2 0 26 34 687 0 0 679 3
 Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
 Initial Bse: 0 0 2 0 24 31 627 0 0 620 3
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Volume: 0 0 0 2 0 24 31 627 0 0 620 3
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
 Reduced Vol: 0 0 0 2 0 24 31 627 0 0 620 3
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 MUF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Final Vol.: 0 0 0 2 0 24 124 627 0 0 620 3
 Saturation Flow Module:
 Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Lanes: 0.00 2.00 0.00 0.14 0.86 1.00 0.44 1.56 0.00 0.00 1.99 0.01
 Final Sat.: 0 3000 0 214 1286 1500 659 2341 0 0 2987 13
 Capacity Analysis Module:
 Vol/Sat: 0.00 0.00 0.00 0.01 0.00 0.02 0.05 0.27 0.00 0.00 0.21 0.21
 Crit Vol: 0 24 402
 Crit Moves: ****

Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 PM Peak

Level of Service Computation Report
 Circular #92 ICF Driveaway # 1 / Sepulveda Blvd
 Intersection #92 ICF Driveaway # 1 / Sepulveda Blvd
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.516
 Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
 Optimal Cycle: 38 Level Of Service: A
 Approach: North Bound East Bound West Bound
 Movement: L - T - R L - T - R L - T - R L - T - R L - T - R
 Control: Permitted Permitted Permitted Permitted Permitted
 Rights: Include Include Include Include Include
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
 Lanes: 0 0 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0
 Volume Module:
 Base Vol: 21 2 33 127 4 176 100 690 33 23 680 7
 Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
 Initial Bse: 19 2 30 116 4 161 91 630 30 21 621 6
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 PHF Volume: 19 2 30 116 4 161 91 630 30 21 621 6
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
 Reduced Vol: 19 2 30 116 4 161 91 630 30 21 621 6
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 MUF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Final Vol.: 19 2 30 116 4 161 91 630 30 21 621 6
 Saturation Flow Module:
 Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
 Lanes: 0.37 0.04 0.59 1.00 0.01 0.99 1.00 1.91 0.09 1.00 2.97 0.03
 Final Sat.: 534 51 840 1425 14 1411 1425 2720 130 1425 4231 44
 Capacity Analysis Module:
 Vol/Sat: 0.04 0.04 0.04 0.08 0.26 0.11 0.06 0.23 0.23 0.01 0.15 0.15
 Crit Vol: 19 365
 Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #93 ICTF Driveway # 2 / Sepulveda Blvd
Cycle (sec): 100 Critical Vol./Cap.(X): 0.398
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 31 Level Of Service: A
Approach: North Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Protected Protected
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 1 0 0 1 0 1 0 1 0 1 0 1 0 1 0 2 1 0

Volume Module:
Base Vol: 50 1 93 17 0 5 6 770 54 98 612 3
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 46 1 85 16 0 5 5 703 49 89 559 3
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 46 1 85 16 0 5 5 703 49 89 559 3
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 46 1 85 16 0 5 5 703 49 89 559 3
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 46 1 85 16 0 5 5 703 49 89 559 3

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 0.01 0.99 1.00 0.00 1.00 1.00 1.87 0.13 1.00 2.99 0.01
Final Sat: 1425 15 1410 1425 0 1425 1425 2663 187 1425 4254 21

Capacity Analysis Module:
Vol/Sat: 0.03 0.06 0.06 0.01 0.00 0.00 0.00 0.26 0.26 0.06 0.13 0.13
Crit Vol: 86 16 376 89
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #94 Santa Fe Ave / Anaheim St
Cycle (sec): 100 Critical Vol./Cap.(X): 0.470
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 43 Level Of Service: A
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 1 0 1 1 0 1 0 1 0 1 0 2 1 0 1 0 3 0 1

Volume Module:
Base Vol: 45 141 53 197 159 77 74 803 18 33 730 188
Growth Adj: 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06 1.06
Initial Bse: 48 149 56 208 168 81 78 850 19 35 772 199
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 48 149 56 208 168 81 78 850 19 35 772 199
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 48 149 56 208 168 81 78 850 19 35 772 199
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 48 149 56 208 168 81 78 850 19 35 772 199

Saturation Flow Module:
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.45 0.55 1.00 1.35 0.65 1.00 2.93 0.07 1.00 3.00 1.00
Final Sat: 1375 1999 751 1375 1853 897 1375 4035 90 1375 4125 1375

Capacity Analysis Module:
Vol/Sat: 0.03 0.07 0.07 0.15 0.09 0.09 0.06 0.21 0.21 0.03 0.19 0.14
Crit Vol: 103 208 78
Crit Moves: ****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #110 John S. Gibson / Channel Street

Cycle (sec): 100 Critical Vol./Cap.(X): 0.600
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 47 Level Of Service: B

Approach: North Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted	Include	Protected	Permitted	Include	Protected	Permitted	Include
Rights:	0	0	0	0	0	0	0	0
Min. Green:	1	0	2	0	1	1	0	1
Lanes:	1	0	2	0	1	1	0	1

Volume Module:
Base Vol: 380 512 0 0 354 262 491 0 393 0 0 0
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 347 467 0 0 323 239 448 0 359 0 0 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 347 467 0 0 323 239 448 0 359 0 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 347 467 0 0 323 239 448 0 359 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 347 467 0 0 323 239 448 0 359 0 0 0

Saturation Flow Module:
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 2.00 0.00 0.00 2.00 1.00 1.66 0.01 1.33 0.00 0.00 0.00
Final Sat.: 1425 2850 0 0 2850 1425 2374 0 1901 0 0 0

Capacity Analysis Module:
Vol/Sat: 0.24 0.16 0.00 0.00 0.11 0.17 0.19 0.00 0.19 0.00 0.00 0.00
Crit Vol: 347 239
Crit Moves: *****

Port of Los Angeles
West Basin Terminal Improvement
Year 2000 PM Peak

Level of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #128 Broad Ave / Harry Bridges Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.285
Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
Optimal Cycle: 20 Level Of Service: A

Approach: North Bound East Bound West Bound
Movement: L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted	Include	Protected	Permitted	Include	Protected	Permitted	Include
Rights:	0	0	0	0	0	0	0	0
Min. Green:	0	1	0	0	1	0	0	1
Lanes:	0	1	0	0	1	0	0	1

Volume Module:
Base Vol: 1 7 95 5 3 53 126 555 0 28 259 31
Growth Adj: 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91 0.91
Initial Bse: 1 6 87 5 3 48 115 507 0 26 236 28
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 1 6 87 5 3 48 115 507 0 26 236 28
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 1 6 87 5 3 48 115 507 0 26 236 28
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Vol: 1 6 87 5 3 48 115 507 0 26 236 28

Saturation Flow Module:
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 0.02 0.98 1.00 0.16 0.84 1.00 0.37 1.63 0.00 0.19 1.63 0.18
Final Sat.: 29 1471 1500 246 1254 1500 555 2445 0 230 2442 269

Capacity Analysis Module:
Vol/Sat: 0.03 0.00 0.06 0.02 0.00 0.03 0.21 0.21 0.00 0.09 0.10 0.11
Crit Vol: 87 5
Crit Moves: *****

 Port of Los Angeles
 West Basin Terminal Improvement
 Year 2000 PM Peak

Level of Service Computation Report
 Circular 212 Planning Method (Base Volume Alternative)

 Intersection #212 Navy Way / Seaside Ave
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.472
 Loss Time (sec): 0 (Y+R=4.0 sec) Average Delay (sec/veh): xxxxxx
 Optimal Cycle: 35 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
 Movement: L - - T - - R L - - T - - R L - - T - - R L - - T - - R

Control:	Permitted		Protected		Protected	
Rights:	Ignore	Include	Include	Include	Include	Include
Min. Green:	0	0	0	0	0	0
Lanes:	2	0	0	0	3	0
	1	0	0	0	1	2
	0	0	0	0	3	0
	0	0	0	0	0	0

Volume Module:

Base Vol:	108	0	656	0	0	0	1438	72	206	1333	0
Growth Adj:	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06	1.06
Initial Bse:	114	0	694	0	0	0	1521	76	218	1410	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	114	0	694	0	0	0	1521	76	218	1410	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	114	0	694	0	0	0	1521	76	218	1410	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Vol.:	114	0	694	0	0	0	1521	76	218	1410	0

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	2	0	0	0	0	0	3	0	1	2	0
Final Sat.:	2850	0	1425	0	0	0	4275	1425	2850	4275	0

Capacity Analysis Module:

Vol/Sat:	0.04	0.00	0.00	0.00	0.00	0.00	0.36	0.05	0.08	0.33	0.00
Crit Vol:	57	0	507	0	0	507	109	507	109	507	0
Crit Moves:	57	0	507	0	0	507	109	507	109	507	0